

# EK-L Super K 0-0-6

## With 2% Sulfur



Manufactured & Guaranteed by:  
**EnviroKure, Incorporated**  
[www.EnviroKure.com](http://www.EnviroKure.com)

5222 E Comly Street, Philadelphia, PA 19135  
215-289-9800

**0 – 0 – 6 – 2S**

### **Guaranteed Analysis**

Total Nitrogen (N) **0%**

0% Ammoniacal Nitrogen

0% Water Soluble Nitrogen

Phosphorus (P<sub>2</sub>O<sub>5</sub>) **0%**

Soluble Potash (K<sub>2</sub>O) **6%**

Sulfur (S) **2%**

**Derived from:** chicken manure, sulfate  
of potash

### **Directions for use**

Use in accordance with recommendations of a qualified individual or institution or in accordance with recommendations of your approved Nutrient Management Plan (NMP).

#### **CAUTION: KEEP OUT OF REACH OF CHILDREN**

Wash hands and face before eating or drinking. Wash soiled clothing before wearing again if contact occurs.

**EYES:** Contact can cause mild irritation of eyes. Flush with running water. Seek medical attention if irritation persists.

**SKIN:** Wash thoroughly with soap & water. Seek medical attention if rash develops.

**IF SWALLOWED:** Drink one or two glasses of water and induce vomiting. Seek immediate attention. Never induce vomiting or give anything by mouth to an unconscious person.

**INHALATION:** Move to fresh air. If irritation persists, get medical attention.

NOTICE: Seller warrants that this product conforms to its chemical description and is reasonably fit for the purposes stated on the label when used according to directions under normal conditions on most agricultural crops. Because of widely varying use conditions, it is impossible to eliminate all risks even when the label directions are followed. Therefore, the manufacturer makes no other warranties, expressed or implied. The buyer assumes all risks associated with the use of this product. In the event of damage resulting from a breach of warranty, the buyer agrees to accept a refund of the purchase price as full discharge of the manufacturer's liability

**275 US Gallons Net Wt 2,558 lbs.**

**Density: 9.3 lbs/gal at 68 degrees Fahrenheit**